

Relative and differential pressure module type 698

Pressure range

-5 ... 5 mbar / 0 ... 1 – 10000 mbar

The pressure modules type 698 are suitable for monitoring pressure and flow in air conditioning systems and in the laboratory sector.

The module is optionally available with a 3 digit LED display, two limit value switches (potential free) as well as a square root extraction.



- Rugged measured value detector, owing to outstanding synergy obtained by combining diaphragm technology with a ceramic element
- High overpressure safety margin, even in the lowest pressure range
- Easy to install and commission
- No maintenance required

Technical overview

Pressure range

Relative	-1 ... 0 bar
	0 ... 10 bar
Differential	-5 ... 5 mbar
	0 ... 500 mbar

Operating conditions

Medium		Air and neutral gases
Temperature	Medium	0 ... +70 °C
	Ambient	-10 ... +70 °C
	Storage	-40 ... +70 °C
Tolerable overload on one side	Differential pressure	0 ... 50 mbar
	Relative pressure	0.1 ... 10 bar
Rupture pressure	Differential pressure	0 ... 50 mbar
	Relative pressure	100 ... 500 mbar
		5x fs
		3x fs ¹⁾

Materials in contact with the medium

Pressure connections	PVC
Hose connection	Silicone / PA
Diaphragm	Silicone / Al ₂ O ₃ (96%) / Silicium
Sensor housing	PA, PC, Ultem
Sealing material	NBR
Sensor	Al ₂ O ₃ (96%) / Silicium

Electrical overview

Output (Selectable by customer)	0 ... 10 V	
	0 ... 20 mA	
	4 ... 20 mA	
Power supply	17 ... 33 VDC	
	24 VAC	
	115 VAC	
	230 VAC	
Tolerable load	0 ... 10 V	
	> 2 kOhm	
Current consumption	0 ... 20 mA / 4 ... 20 mA	
	< 500 Ohm	
Polarity reversal protection	< 4 VA	
	Extra-low voltage	Each connection is protected against crossover up to max. power supply
	Low voltage	230 VAC / 115 VAC only on supply terminals, transformer short-circuit

Dynamic response

Response time	< 20 ms
Load cycle	< 10 Hz

Protection standard

IP 65

Limit switches

Two potential free change over contacts adjustable over the full range (Adjustment with potentiometer).	
Contact rating	250 VAC / 6A
Switching hysteresis	~ 1% fs fixed

Electrical connection

Screw terminals for 1.5 mm ²

Pressure connection

Connection pipe (conical)	Ø 4 ... 7 mm
Quick fitting	Ø 3.9 mm / M6x0.75

Display

LED, 3 digit

Mounting instruction

Installation arrangement	Unrestricted ²⁾
Mounting	Fixing holes integrated in housing

Tests / Admissions

Electromagnetic compatibility	CE conformity acc. EN 61326-2-3
-------------------------------	---------------------------------

Weight

24 VDC, without display	~ 440 g
230 VAC, with display	~ 640 g

Packaging

Single packaging in cardboard

¹⁾ max. 14 bar at 20 °C and max. 7 bar at 70 °C

²⁾ Positional error versions with full scale ≤ 50 mbar = 0.13 mbar

Accuracy

Parameter	Transmitter type	Unit	-0.5 ... +0.5 mbar 0 ... 1 mbar	-5 ... +5 mbar 0 ... 3 - 500 mbar	-1 ... 0 bar 0 ... 1 - 6 bar
Tolerance zero point	max.	% fs	± 1.0	± 0.7	± 0.7
Tolerance full scale	max.	% fs	± 1.0	± 0.7	± 0.7
Resolution		% fs	0.2	0.1	0.1
Total of linearity, hysteresis and repeatability		% fs	± 2.5	± 1.0	± 1.0
Long term stability acc. DIN EN 60770		% fs	± 1.0	± 1.0	± 0.5
TC zero point ¹⁾	max.	% fs/10K	± 1.0	± 0.5	± 0.3
TC sensitivity ¹⁾	max.	% fs/10K	± 0.6	± 0.5	± 0.2

With root-extracted output (2 ... 100% pressure)
Absolute error: (% of full scale)

TC zero point: % fs/10K ¹⁾

0 ... 1 mbar
max. $\pm 0.6 \sqrt{\frac{p_{fs}}{p}} + 1.5$

0 ... 3 mbar - 6 bar
max. $\pm 0.3 \sqrt{\frac{p_{fs}}{p}} + 1.5$

max. $\pm 0.6 \sqrt{\frac{p_{fs}}{p}} + 1.5$

Test conditions:
25 °C, 45% RH, power supply 24VDC
TC z.p. / TC s. -10 ... +50 °C





Order code selection table

698. X X X X X X X X X X

Version	without limit switches	0																				
	with limit switches	1																				
Pressure range	-5 ... + 5 mbar	Differential pressure	0	0						0												
	-0.5 ... + 0.5 mbar	Differential pressure	0	1						0												
	-0.5 ... + 1 mbar	Differential pressure	0	2						0												
	-0.5 ... + 3 mbar	Differential pressure	0	3						0												
	-0.5 ... + 5 mbar	Differential pressure	0	4						0												
	0 ... + 1 mbar	Differential pressure	0	5																		
	0 ... + 3 mbar	Differential pressure	0	6																		
	0 ... + 5 mbar	Differential pressure	0	7																		
	0 ... + 10 mbar	Differential pressure	0	8																		
	0 ... + 30 mbar	Differential pressure	1	0																		
	0 ... + 50 mbar	Differential pressure	1	1																		
	0 ... + 100 mbar	Differential pressure	1	2																		
	0 ... + 200 mbar	Differential pressure	1	3																		
	0 ... + 500 mbar	Differential pressure	1	4																		
Pressure unit ²⁾	mbar / bar									0												
	Pa	for pressure ranges ≤ 10 mbar								1												
	kPa	for pressure ranges 3 mbar ... 6 bar								2												
	MPa	for pressure ranges 2.5 bar ... 10 bar								3												
	Power supply	17 ... 33VDC / 24VAC ± 15%									0											
		24 VAC	galvanically isolated								1											
		115 VAC	galvanically isolated								2											
		230 VAC	galvanically isolated								3											
	Output	0 ... 10V																				0
		0 ... 20mA																				1
4 ... 20mA																					2	
Square root extraction	Without root extraction																				0	
	With root extraction																				1	
Display	Without display																				0	
	In pressure unit chosen above																				0	
	With display in %																				2	
Pressure connection	Connection pipe																				0	
	Quick fitting																				1	
Installation arrangement	Horizontal																				0	
	Vertical																				1	

¹⁾ TC = Temperature coefficient

²⁾ Other pressure units on request





FOR FINE PRESSURE AND FLOW MEASUREMENT

Huba Control AG
Headquarters

Industriestrasse 17
5436 Würenlos
Telefon +41 (0) 56 436 82 00
Telefax +41 (0) 56 436 82 82
info.ch@hubacontrol.com

Huba Control AG
Niederlassung Deutschland

Schlattgrabenstrasse 24
72141 Walddorfhäslach
Telefon +49 (0) 7127 23 93 00
Telefax +49 (0) 7127 23 93 20
info.de@hubacontrol.com

Huba Control SA
Succursale France

Rue Lavoisier
Technopôle Forbach-Sud
57602 Forbach Cedex
Téléphone +33 (0) 387 847 300
Télécopieur +33 (0) 387 847 301
info.fr@hubacontrol.com

Huba Control AG
Vestiging Nederland

Hamseweg 20A
3828 AD Hoogland
Telefoon +31 (0) 33 433 03 66
Telefax +31 (0) 33 433 03 77
info.nl@hubacontrol.com

Huba Control AG
Branch Office United Kingdom

Unit 13 Berkshire House
County Park Business Centre
Shrivenham Road
Swindon - Wiltshire SN1 2NR
Phone +44 (0) 1993 776667
Fax +44 (0) 1993 776671
info.uk@hubacontrol.com

www.hubacontrol.com